

PRODUCT DATA SHEET

XREV Fully Synthetic Engine Oil is an automotive lubricant with a proprietary blend of ultra high performance synthetic basestocks fortified with a precisely balanced system of component additives:

- Meets or exceeds the latest OEM and industry approvals
- Provides excellent overall performance for latest engine types
- Excellent low temperature abilities for quick protection for the engine at start up
- Contains special proprietary friction modification additives which enhances performance, reduces wear and tear, as well and improves fuel economy
- Reduces deposits and acid build up even in extreme conditions
- Provides exceptional cleaning power for all engines

TYPICAL PROPERTIES

| | Xrev Engine Treatment Lubricants (Fully Synthetic) | | |
|-----------------------|---|-------------|-------------|
| | 0W – 30 | 0W- 40 | 15W - 50 |
| API | SN/SM/SL | SN/SM/SL | SN/SM/SL |
| ACEA | A3/B3 A3/B4 | A3/B3 A3/B4 | A3/B3 A3/B4 |
| Viscosity, ASTM D 445 | | | |
| cSt at 40° C | 68 | 92.2 | 138 |
| cSt at 100° C | 10.2 | 14.0 | 18.5 |
| Viscosity Index | 164 | 185 | 189 |
| Pour Point C | - 25 | - 25 | - 25 |
| Flash Point C | 233 | 235 | 238 |
| Density at 15° C Kg/l | 0.80 | 0.87 | 0.88 |
| ASTM D 4052 | | | |

Approved for : VW: 502 00/503 01/ 505 00/507 00 Daimer Chrysler FIAT FIAT 9.55535 – M2, N2, Z2 MB 229.3/ 229.5 BMW Longlife-04 OPEL Long Life Service Fill GM-LL-A-025 Porsche A40



Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

All trademarks used herein are trademarks or registered trademarks of Xtreme Xrev International Corporation.

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, visit <u>www.x-lube.com</u>

Copyright © 2005-2015 Xtreme Xrev International Corporation. All rights reserved..